



Web:
www.ultrasonicpartswashers.com

Email:
ultrasonicpartswashers@comcast.net



High Performance Ultrasonic System

- Rugged Stainless Steel Construction and Plumbing
- Programmable Digital Control: Tank Warm-up, Temperature, Cycle Time
- Eastern Precision Cleaning Systems incorporate the power of Ceramically Enhanced Transducers to provide effective ultrasonic cleaning

Environmentally Sound Cleaning

Voltage	230 Volts, 1 Phase, 60 Hz
Amps	28 Amps
Heat Power in watts rms	4000 Watts of Strip Heat
Operating Temperature	130-160
Ultrasonic Power in watts rms	2000 Watts RMS of Ultrasonic Power
Ultrasonic Standard kHz	40 kHz
Overall Dimensions LR	41.5"
Overall Dimensions FB	35.25"
Overall Dimensions HT	36.5"
Capacity Gallons	42 Gallons Working Solution
Working Tank LR	35"
Working Tank FB	23"
Working Tank Liquid Depth	14.5' Deep (12" Working Depth)
Basket LR	32"
Basket FB	20"
Basket Depth	6"
Wheels	None
Pump	5 GPM Recirculation /Filtration System
Filtration	120 & 50 Micron Cartridge Filters
Surface Sparger	Yes

CALL 1 800 458-0355