



EP3523P

www.ultrasonicpartwashers.com

- Rugged Stainless Steel Tank and Heavy Steel Frame Construction
- Programmable Digital Control: Tank Warm-up, Temperature, Cycle Time
- Eastern Precision Cleaning Systems incorporate the power of Ceramically Enhanced Transducers and adjustable Generators to provide superior ultrasonic cleaning.
- Standard 2 Stage Filtration with optional Oil Skimmer

Environmentally Sound Cleaning

| | |
|--------------------------------------|---|
| Voltage | 230 Volts, 1 Phase, 60 Hz |
| Amps | 28 Amps |
| Heat Power in watts rms | 4000 Watts of Strip Heat |
| Operating Temperature | 130-180 |
| Ultrasonic Power in watts rms | 2000 Watts RMS of Ultrasonic Power |
| Ultrasonic Standard kHz | 40 kHz |
| Overall Dimensions LR | 41.5" |
| Overall Dimensions FB | 35.25" |
| Overall Dimensions HT | 36.5" |
| Capacity Gallons | 42 Gallons Working Solution |
| Working Tank LR | 35" |
| Working Tank FB | 23" |
| Working Tank Liquid Depth | 14.5' Deep (12" Working Depth) |
| Basket LR | 32" |
| Basket FB | 20" |
| Basket Depth | 6" |
| Wheels | 4" Casters |
| Pump | 5 GPM Recirculation /Filtration System |
| Filtration | Wye Strainer / Dual 10" Cartridge Filters |
| Surface Sparger | Yes |

CALL 1 800 458-0355